



ULTRAFOAM



A concentrated alkaline foaming liquid detergent for cleaning surfaces and equipment.







ULTRAFOAM



ADVANTAGES

- Highly foaming, wetting, emulsifying and complexing detergent.
- Very active even in the presence of hard water and low temperatures.
- Great dragging capacity and emulsion of organic matter.
- Easy rinsing.
- With corrosion inhibitors to protect materials.
- To be used in pig, poultry, sheep and cattle houses.













Surfaces / Equipment / Vehicles

Prepare a solution with 1% to 4% concentration, depending on level of soiling.

Spray and Foam Application

Apply the solution with 0.3l/m² up to the limit of runoff through spraying or foaming on surfaces and equipment.

Use a pressure washer at low pressure (500 psi) or a foam lance.

Leave on for 20 to 45 minutes.

Rinse thoroughly with water after use.

Dip Application

Equipment can also be dipped. Rinse equipment with water after cleaning.

m²	Solution (I)	ULTRAFOAM			
		1%	2%	3%	4%
10	3	30 ml	60 ml	90 ml	120 ml
100	30 I	0.3	0.6	0.9	1.2
1,000	300	3	6 I	9	12 l
10,000	3.000	30 I	60 I	90 I	120 l



Active Substance: Sodium hydroxide

12.2±0.2 pH at 10g/l:

Store in a cool, dry place in the original container. Storage:

Keep pack tightly closed.

Shelf Life: 12 months from date of manufacture

